



Electrical Connections



www.st-templin.com



more than 66 years
quality in motion



Electrical coils, 7-pole


general specifications:

PUR or Hytrel

metal- or plastic plug

according to ISO 1185 (N) and ISO 3731 (S)

working length from 3,5 m to 5,5 m



12 V

PUR, 41 turns / inner Ø 19 mm, working length 3,5 m,
metal plug ISO 1724

01.010.7200.330

Hytrel, 19 turns / inner Ø 50 mm, working length 3,5 m,
metal plug ISO 1724

01.010.7200.060

12 V / 24 V

PUR, 41 turns / inner Ø 19 mm, working length 3,5 m,
metal plug ISO 1724,1185

01.010.7200.320

PUR, 55 turns / inner Ø 19 mm, working length 5,5 m,
metal plug ISO 1724,1185

01.010.7200.350

24 V

PUR, 41 turns / inner Ø 19 mm, working length 3,5 m,
plastic plug type N; ISO 1185

01.010.7200.310

PUR, 41 turns / inner Ø 19 mm, working length 3,5 m,
metal plug type N; ISO 1185

01.010.7200.316

PUR, 41 turns / inner Ø 19 mm, working length 3,5 m,
plastic plug type S; ISO 3731

01.010.7200.340

PUR, 46 turns / inner Ø 19 mm, working length 3,5 m,
metal plug type S; ISO 3731

01.010.7200.346

Hytrel, 19 turns / innerØ 50 mm, working length 3,5 m,
metal plug type N; ISO 1185

01.010.7200.040



more than 66 years
quality in motion



EBS- Electrical coils, 7-pole

general specifications:

PUR or Hytrel

plastic plug according to ISO 7638

working length 3,5 m to 3,8 m



24 V

PUR, 30 turns / inner Ø 30 mm, working length 3,8 m

01.010.7201.441

Hytrel, 16 turns / inner Ø 60 mm, working length 3,5 m

01.010.7201.440

Electrical coils, 15-pole

general specifications:

PUR or Hytrel

plastic plug according to ISO 12098

working length 4,5 m



24 V

PUR, 34 turns / inner Ø 30 mm, working length 4,5 m

01.010.7210.189

Hytrel, 16 turns / inner Ø 70 mm, working length 4,5 m

01.010.7210.200



more than 66 years
quality in motion



Adapter cable, 1x 15-pole to 2x 7-pole

general specifications:

PUR

optional with special configurations

working length 3,0 m



12-core configuration, 24 V

PUR, 2x 33 turns / inner Ø 19 mm, working length 3,0 m,
plastic plug type N / S; ISO 1185, 3731 & plastic plug; ISO 12098

01.010.7215.000

13-core configuration, 24 V

PUR, 2x 33 turns / inner Ø 19 mm, working length 3,0 m,
plastic plug type N / S; ISO 1185, 3731 & plastic plug; ISO 12098

01.010.7215.030

All ST-Templin electrical connections guarantee:

- best cold- / heat-resistance
- excellent recoil
- high resistance against oil and chemicals
- components (e.g. plugs) are available separately.

Special configurations are available on request.

ST-Templin GmbH

Domänenweg 1

31863 Coppnenbrügge

Servicehotline: +49 5156 - 96100 - Fax: + 49 5156 - 961196

info@st-templin.com - www.st-templin.com